


Part No. **36967**

10M STANDARD HDMI, ANTHRA LINE

HDMI MALE TO MALE



DESCRIPTION

- Superior performance and design Standard HDMI 2.0 cable
- Supports UHD resolutions up to 4096x2160@60Hz 4:2:0 8bit
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant bare copper 24AWG conductors
- HDMI 2.0 compliant, 3D, 4K, 10.2Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 24AWG copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:2:0 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

These HDMI 2.0 cables support 10.2Gbps bandwidth capacity in cable lengths from 7.5m up to 20m.

Anthra Line HDMI cables are available in lengths from 0.3m to 20m.

RELATED PRODUCTS

37876, 37866

10M STANDARD HDMI, ANTHRA LINE

CONNECTORS

Connector A	HDMI Type A Male
Connector B	HDMI Type A Male
Housing Material	PVC
Connector Plating	Gold
Pin Construction	Phosphor Bronze
Pin Plating	Gold
Dimensions (approx.) WxDxH	21.4x41.44x12.7mm (0.84x1.63x0.5in)

CABLE CONSTRUCTION

Length	10m [32.81ft]
Standard	HDMI Standard
Colour	Black
Type	Round
Jacket Diameter	9.8mm [0.39in]
Jacket Material	PVC
Conductor Material	Bare Copper
Conductor Gauge	24AWG
Shielding	Aluminium Magnesium Alloy 55%

SPECIFICATONS

Supported Bandwidth	10.2Gbps
Maximum Resolution	4096x2160@60Hz 4:2:0 8bit
Nominal Attenuation	300kHz-825MHz --- 15dB 825MHz-2.475GHz --- 15 - 29dB 2.475GHz-4.125GHz --- 29 - 44dB
Minimum Bend Radius	98mm [3.86in]
Operating Temperature	-20°C - 80°C [-4°F - 176°F]
Storage Temperature	-25°C - 85°C [-13°F - 185°F]

MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	10
Certificated	RoHS, REACH, UL

PURCHASING INFORMATION

No.	36967
EAN	4002888369671

AVAILABLE IN OTHER LENGTHS

36966 - 7.5m [24.61ft]
36967 - 10m [32.81ft]
36968 - 15m [49.21ft]
36969 - 20m [65.62ft]