



2m C14 Plug to UK 3-Pin Socket Power Cable

30483

TITLE EN

2m C14 Plug to UK 3-Pin Socket Power Cable

SUBTITLE EN

C14 to UK 3-Pin Socket Cable 1-gang mains extension socket

SHORT DESCRIPTION EN

- C14 Plug to UK 3-Pin Socket Power Cable for use in professional areas and private sectors
- Rated to 10A/250V
- Robust PVC housing and cable jacket, lead-free connectors (<0.1% lead in brass)
- High temperature resistance allows the cable to be used in non air-conditioned areas
- 10 year warranty

Designed to provide extended power connectivity, free from the constraints of the original power cable's length. These cables are ideal for use with iPower PDU products, this makes them an excellent choice for integrating a variety of devices ensuring seamless and efficient power distribution across your setup. This makes it a perfect solution for a range of environments, including offices, control rooms, digital signage setups, and home theatres.

This cable is built for convenience and reliability ensuring seamless power delivery to your device, however, it is important to note that it is intended for use in dry areas only. For safety and optimal performance, ensure that the total rating of the connected devices does not exceed 10A or the rating of the IEC socket on the UPS or IEC distribution board being used. With its robust functionality and versatility, this cable is an essential tool for creating flexible and efficient device setups.

The brass used in the connectors has a lead content of far below 0.1% and is therefore SVHC-free, as are all other materials used in these cables.

LONG DESCRIPTION EN

Connectors

- Connector A: IEC C14
- Connector B: UK 3-Pin Socket
- Housing Material: PVC & PBT
- Pin Construction:
 1. A: Brass
 2. B: Phosphor Bronze
- Pin Plating: Nickel
- Dimensions (approx.) WxDxH:
 1. A: 40x30x20mm (1.57x1.18x0.78in)
 2. B: 60x95x30mm (2.36x3.74x1.18in)

Cable Construction

- Length: 2m (6.56ft)
- Colour: Black
- Conductor Material: Copper
- Cable Material: H05VV-F 3G1.0mm²
- Number of Wires: 3
- Wire Gauge: 1.0mm²
- Jacket Diameter: 8mm (0.31in)
- Jacket Material: PVC

Specifications

- Rated Current and Voltage: 10A/250V
- Operating Temperature: -10°C - 60°C (14°F - 140°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: UKCA, CE, RoHS, REACH

Purchasing Information

- No.: 30483
- EAN: 4002888304832

This product is also available in other lengths

- 30481 - 0.5m (1.64ft)
- 30482 - 1m (3.28ft)
- 30483 - 2m (6.56ft)
- 30484 - 3m (9.84ft)
- 30485 - 5m (16.44ft)