



36473

WEB PICS



TITLE EN

3m High Speed HDMI Cable, Black Line

SUBTITLE EN

HDMI® Male to Male

SHORT DESCRIPTION EN

- Entry level High Speed HDMI® cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 8bit
- Robust PVC housing, nickel connectors, 24K gold plated contacts
- Triple shielded cable, corrosion resistant copper coated steel 30AWG conductors
- 10 year warranty

From the lines cable connectivity concept developed by Lindy, Black Line High Speed HDMI® cables are fully featured, entry level high resolution connection solutions, perfect for home and small office use.

Black Line High Speed HDMI® cables feature triple shielded construction with 30AWG copper coated steel conductors for premium performance and corrosion resistance. Nickel connectors and gold flashed contacts maintain signal integrity and reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Black Line HDMI® cables are also capable of transmitting 32 channel audio and Dolby True HD.

Black Line HDMI® cables are available in lengths from 0.5m, 1m, 2m, 3m and 5m

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



LONG DESCRIPTION EN

Connectors

- Connector A: HDMI® Type A Male
- Connector B: HDMI® Type A Male
- Housing Material: PVC
- Connector Plating: Nickel
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold Flash
- Dimensions (approx.) WxDxH: 19.2x34.1x10.6mm (0.76x1.34x0.42in)

Cable Construction

- Length: 3m (9.84ft)
- Standard: High Speed HDMI® with Ethernet
- Colour: Black
- Type: Round
- Jacket Diameter: 5.5mm (0.22in)
- Jacket Material: PVC
- Conductor Material: Copper Coated Steel
- Conductor Gauge: 30AWG
- Shielding: Aluminium Foil

Specifications

- Supported Bandwidth: 18Gbps
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit
- Nominal Attenuation:
 - 300kHz-825MHz <5dB
 - 825MHz-2.475GHz <5dB
 - 2.475GHz-4.125GHz <12dB
 - 4.125GHz-5.1GHz <20dB
- Minimum Band Radius: 22mm (0.87in)
- Operating Temperature: -10°C - 80°C (14°F - 176°F)
- Storage Temperature: -30°C - 85°C (-22°F - 185°F)
- ATC Approved: No

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: RoHS, REACH, UL

Purchasing Information

- No.: 36473
- EAN: 4002888364737

This product is also available in other lengths

- 36470 - 0.5m (1.64ft)
- 36471 - 1m (3.28ft)
- 36472 - 2m (6.56ft)
- 36473 - 3m (9.84ft)
- 36474 - 5m (16.44ft)